



ALUMINUM BODY

MAXIMUM O.A.H. 125.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

- AIR INLET WITH DISCONNECT COUPLING LOCATED IN DRIVER LOWER STEP WELL OF CAB
- STEERING LOCK MECHANISM FRONT AND REAR
- STAINLESS STEEL FENDER CROWNS FRONT AND REAR
- STANDARD 1500 BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
- BATTERY CHARGER INDICATOR LOCATED IN DRIVER SEAT RISER
- BOASTING BRACE FOR ANTENNA LOCATED PER SHOP ORDER #1
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS D1, P1 AND P2
- ONE ADJUSTABLE 1111-104-020 TRAY IN COMPARTMENT B1
- ONE VERTICAL PARTITION IN COMPARTMENT D2
- DRY-DECK MATTING WITH BEVEL ON FLOOR IN COMPARTMENTS D2, D3 AND P2
- DRY-DECK MATTING LOCATED ON ALL SHELVES AND TRAYS
- ONE ADJUSTABLE SHELVING IN COMPARTMENTS D2, P1 AND P2
- ONE HANNAY BOOSTER HOSE REEL MODEL EP32-21-22-B WITH 150' OF 1.00\"/>

CUSTOMER APPROVAL
APPROVED BY: _____
DATE: _____

Unitender Pierce MANUFACTURING INC.				JOB NO.	22719
				SCALE	1:24
				DATE	23SEP09
				CHANGED BY	KBO
				DATE	25SEP09
				SHEET SIZE	D
				SHEET NO.	1 of 1

REV	DATE	BY	CH	CONTENDER	NO.	22719AD