



ALUMINUM BODY MAXIMUM O.A.L. 397.50"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

- PIERCE LOGO MOUNTED FORWARD AND REARWARD OF REAR WHEELS
- 5/8" X 1/8" END RINGS LOCATED FRONT AND REAR
- 5/8" SPLIT SCUFFPLATE ON EACH CAB DOOR JAMB
- 5/8" SPLIT SCUFFPLATE ON REAR CORNERS OF CREW CAB
- MOUNTING BASES FOR ANTENNAS LOCATED PER SHOP ORDER
- DUAL 100 BATTERY CHARGER LOCATED IN PUMP PLUMBING AREA
- 5/8" SPLIT SCUFFPLATE IN P.S. PIPE POLE/ FOLDING LADDER COMPARTMENT
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS D1, P1 & R1
- URI-DECK MATTING LOCATED ON ALL SHELVES AND TRAYS
- ONE ADJUSTABLE TILTING SLIDE OUT TRAY LOCATED IN COMPARTMENT P2
- ONE VERTICAL DIVIDER IN COMPARTMENT D3
- COMPARTMENT VENTILATION SYSTEM
- ONE ADJUSTABLE SHELVES LOCATED IN COMPARTMENTS D1, P1, P3, TWO IN D3 & P4
- ONE HANNAY ELECTRIC WINDING BOOSTER REEL MODEL 588750-27-28-B LOCATED ON THE REAR WALL IN COMPARTMENT R1 WITH CAPACITY FOR 150' OF 1.00" HOSE AND LEFT NOZZLE
- PERIMETER SCENE LIGHTS LOCATED PER SHOP ORDER
- CIRCUIT BREAKER PANEL LOCATED IN COMPARTMENT D3
- ONE HANNAY ELECTRIC WINDING CORD REEL MODEL 1618-17-18 WITH 200' OF 10/3 CABLE, JUNCTION BOX AND ALUMINUM HOLDER LOCATED IN COMPARTMENT P3
- ONE 15A 120V RECEPTACLE LOCATED IN COMPARTMENT P3 & TWO IN CAB
- ONE 20A 120V DUPLEX RECEPTACLE LOCATED IN COMPARTMENT P4
- ONE ADDITIONAL PAIR OF RUNNINGBOARDS SHIPPED LOOSE

CUSTOMER APPROVAL

APPROVED BY: _____
DATE: _____

30APR10	MEB	KBO	CHASSIS DATA
05JAN10	MEB	KBO	TITLE
10NOV09	MEB	KBO	DATE
07OCT09	MEB	KBO	PIERCE
06OCT09	MEB	KBO	MODEL
REV	DATE	BY	CH

IMP7010

Pierce MANUFACTURING INC.

JOB NO. 22724
01-03

SCALE 1:24

DATE 28SEP09

DRAWN BY MEO

CHECKED BY BZ1

DATE 30SEP09

SHEET SIZE D

SHEET NO. 1 of 1

TITLE: 1500-D-745P, 25 GALLON FOAM CELL, 189" PUC BODY (4) X-LAYS, LADDER THRU BODY, ROLLER SHUTTER COVER FOR MARION COUNTY FIRE DISTRICT #1 SALEM, OREGON

DWG NO. 22724AD